



AT-, T-Profil



Klemmverbinder einseitig

HTD-Profil



Klemmverbinder für einseitige Riemeneinspannung

Profil	Riemenbreite [mm]	BxL [mm]	Typ / Teilung	Ausführung B Anzahl Bohrungen	Ausführung B Bohrungsdurchmesser	m [mm]	a [mm]	a ₁ [mm]	c [mm]	H [mm]
HTD	10	28×41,8	5M	4	5,5	16	25	-	-	8
HTD	15	34×41,8	5M	4	5,5	22	25	-	-	8
HTD	20	45×66	8M	4	9	29	40	-	-	15
AT	25	50×98	AT20	4	9	35	60	20	-	20
T	25	50×58	T5	4	5,5	35	30	15	-	10
T	25	50×78	T10	4	6,5	35	40	20	-	10
T	25	50×98	T20	4	9	35	60	20	-	20
AT	25	50×58	AT5	4	5,5	35	30	15	-	10
AT	25	50×88	AT15 PRO	4	9	35	50	20	-	20
AT	25	50×88	ATS15	4	9	35	50	20	-	20
BAT	25	50×78	BAT10	4	6,5	35	40	20	-	10
HTD	25	44×41,8	5M	4	5,5	32	25	-	-	8
AT	25	50×78	AT10	4	6,5	35	40	20	-	10
HTD	30	55×66	8M	4	9	39	40	-	-	15
T	32	60×78	T10	4	6,5	42	40	20	-	10
T	32	60×98	T20	4	9	42	60	20	-	20
BAT	32	60×78	BATK10	4	6,5	42	40	20	-	10
BAT	32	60×78	BAT10	4	6,5	42	40	20	-	10
T	32	60×58	T5	4	5,5	42	30	15	-	10
AT	32	60×58	AT5	4	5,5	42	30	15	-	10
AT	32	60×78	AT10	4	6,5	42	40	20	-	10
AT	32	60×88	ATS15	4	9	42	50	20	-	20
AT	32	60×98	AT20	4	9	42	60	20	-	20
AT	32	60×88	AT15 PRO	4	9	42	50	20	-	20
HTD	40	71×116	14M	4	11	51	70	-	-	22
AT	50	75×88	AT15 PRO	4	9	60	50	20	-	20
T	50	75×78	T10	4	6,5	60	40	20	-	10
AT	50	75×78	AT10	4	6,5	60	40	20	-	10
T	50	75×58	T5	4	5,5	60	30	15	-	10
AT	50	75×58	AT5	4	5,5	60	30	15	-	10
T	50	75×98	T20	4	9	60	60	20	-	20
BAT	50	75×88	BATK15	4	9	60	50	20	-	20
AT	50	75×98	AT20	4	9	60	60	20	-	20
BAT	50	75×78	BAT10	4	6,5	60	40	20	-	10
BAT	50	75×78	BATK10	4	6,5	60	40	20	-	10
AT	50	75×88	ATS15	4	9	60	50	20	-	20
BAT	50	75×88	BAT15	4	9	60	50	20	-	20
HTD	50	75×66	8M	4	9	59	40	-	-	15
HTD	55	86×116	14M	4	11	66	70	-	-	22
AT	75	110×58	AT5	4	5,5	90	30	15	-	10
AT	75	110×78	AT10	4	6,5	90	40	20	-	10

Profil	Riemenbreite [mm]	BxL [mm]	Typ / Teilung	Ausführung B Anzahl Bohrungen	Ausführung B Bohrungsdurchmesser	m [mm]	a [mm]	a ₁ [mm]	c [mm]	H [mm]
AT	75	110×98	AT20	4	9	90	60	20	-	20
T	75	110×98	T20	4	9	90	60	20	-	20
T	75	110×78	T10	4	6,5	90	40	20	-	10
BAT	75	110×78	BAT10	4	6,5	90	40	20	-	10
AT	75	110×88	ATS15	4	9	90	50	20	-	20
BAT	75	110×88	BAT15	4	9	90	50	20	-	20
BAT	75	110×88	BATK15	4	9	90	50	20	-	20
BAT	75	110×78	BATK10	4	6,5	90	40	20	-	10
T	75	110×58	T5	4	5,5	90	30	15	-	10
AT	75	110×88	AT15 PRO	4	9	90	50	20	-	20
HTD	85	110×66	8M	4	9	94	40	-	-	15
HTD	85	116×116	14M	4	11	96	70	-	-	22