

BRECO[®]-PinLock

Verfügbare Riementypen, -breiten, PinLock-Type / Zulässige Zugkräfte							Stand: September 2015
Riemenbreite		[mm]	25	32	50	75	96 (nur T10/AT10) / 100
T10	PinLock 6	[N]	-	-	-	-	-
	PinLock 10	[N]	300	400	600	900	1200
TK10K6	PinLock 6	[N]	-	-	-	-	-
	PinLock 10	[N]	300	-	600	-	-
TK10K13	PinLock 6	[N]	-	-	-	-	-
	PinLock 10	[N]	-	400	600	900	1200
AT10	PinLock 6	[N]	200	300	400	600	800
	PinLock 10	[N]	400	500	800	1200	1600
ATK10K6	PinLock 6	[N]	-	-	400	-	-
	PinLock 10	[N]	-	300	800	-	-
ATK10K13	PinLock 6	[N]	-	300	400	600	800
	PinLock 10	[N]	-	500	800	1200	1600
T20	PinLock 6	[N]	400	500	800	1200	1600
	PinLock 10	[N]	700	900	1500	2200	3000
AT20	PinLock 6	[N]	500	600	1000	1500	2000
	PinLock 10	[N]	1000	1200	2000	3000	4000
ATK20K13	PinLock 6	[N]	-	-	-	1500	2000
	PinLock 10	[N]	-	-	-	3000	4000

PinLock 6/10: Schlossverbindung mit 6 bzw. 10 Bohrungen für Gewindestifte